

## DATA SHEET

### BENEFITS

#### SCALABILITY

The vSZ-H is a virtualized WLAN controller than is deployed in a private cloud and can easily support networks with tens of thousands of APs and hundreds of thousands of users.

#### FLEXIBILITY

The vSZ-H can be leveraged as a managed WLAN service offering for an almost unlimited number of customers or to benefit a single network deployment.

#### MANAGED WLAN SERVICES AND MULTI-TENANCY

The multi-tenant capabilities of the vSZ-H enable many customers to share a single instance of the vSZ-H, or each managed services customer can have their own virtual instance of the vSZ-H.

#### HIGH AVAILABILITY

The vSZ-H supports Active/Active clustering across multiple data centers for very high availability.

#### COST EFFECTIVE

Customers only purchase licenses for the number of APs that need to be supported and additional licenses can be added for a pay-as-you-grow model.

#### HOTSPOT 2.0 ROAMING SUPPORT

The vSZ-H is the first to support the Wi-Fi Alliance Hotspot 2.0 release 2 specification, which enables mobile devices to automatically discover and select APs for which a roaming arrangement exists.

#### LOCATION CAPABILITIES

The vSZ-H can enable location-based services. These services require the addition of Ruckus Smart Positioning Technology (SPoT).

#### BIG DATA ANALYTICS AND REPORTING

Large-scale Wi-Fi networks generate an enormous amount of data on network performance. The vSZ-H can upload network statistics to the SmartCell Insight (SCI) platform.

### VIRTUAL SMARTZONE™ HIGH SCALE (VSZ-H)

The virtual SmartZone - High Scale (vSZ-H) is a highly scalable and versatile WLAN controller designed to run in a private cloud deployment. It eliminates the difficulties operators are experiencing with building and managing very large-scale WLAN networks, and it is especially well suited to enabling a managed services offering.


vSZ-H can support for tens of thousands of Ruckus access points and hundreds of thousands of subscribers per virtual instance. The vSZ-H provides all control plane functions, with data plane traffic being routed directly from the APs to a separate WLAN gateway. This approach is consistent with the industry trend toward Software Defined Networks (SDN) that split out the control plane from the data plane.

The vSZ-H can be deployed as a private cloud to support one specific network deployment, or to support hundreds or even thousands of managed WLAN networks. The vSZ-H can run on either an open source KVM hypervisor, Hyper-V/Azure, or VMware vSphere hypervisor. The hypervisor function creates the virtual machines (VMs) that the vSZ-H application can run on. As traffic and load increases, the hypervisor can obtain additional resources from the underlying hardware layer to meet the demand. These resources can later be released as circumstances dictate.

The vSZ-H is especially effective at addressing the enormous opportunity in managed WLAN services for enterprises, small and medium business, and public venues. These organizations see WLAN service as business critical, but often do not have the IT infrastructure to support a truly robust deployment. They are looking to service providers to fill the void here, and the vSZ-H is a critical tool in enabling a scalable and cost-effective service.

**FIGURE:1**

This Diagram shows how the vSZ-H would be deployed in an actual network. All control plane traffic flows between the Ruckus access points and the vSZ-H in the cloud. All data plane traffic is routed directly from the Ruckus access points to a WLAN gateway, without passing through the vSZ-H. This greatly simplifies network design as it allows the WLAN Controller function to be consolidated in a national data center, while the WLAN gateway function can reside in regional data center. This approach allows user data to be quickly routed via the most expeditious path to the Internet. Ruckus supports L2oGRE (aka Soft GRE) for this data tunneling function. Soft GRE is supported by most WLAN gateways. The RADIUS Proxy function on the vSZ-H can greatly reduce the RADIUS traffic load on the WLAN gateways.



## HIGHLY SCALABLE AND FULLY FEATURED WLAN CONTROLLER

The vSZ-H has the scale and the feature set for the most demanding service provider applications. It has been designed with Network Function Virtualization (NFV) in mind, a central tenant of which is the decoupling of the application from the underlying hardware. By splitting out the WLAN control plane from the data plane, and then virtualizing the WLAN Controller application, the stage is set for an extremely versatile network deployment that is consistent with emerging industry trends (See figure 1). The vSZ-H WLAN Controller function provides feature-rich access point management, including control over their selforganizing smart networking behaviors such as RF management, load balancing, adaptive meshing, and backhaul optimization. The following are some of the capabilities that are enabled by the vSZ-H WLAN Controller function.

### WLAN RADIO RESOURCE MANAGEMENT

The vSZ-H supports a variety of radio resource management techniques of which the most important is ChannelFly™. This algorithm allows APs to automatically select the optimum 2.4 and 5 GHz channels so as to maximize performance and minimize interference. When properly deployed, ChannelFly can double the capacity of a WLAN network in a high-density environment. The vSZ-H also manages dynamic mesh deployments that make use of the 5 GHz band to backhaul AP traffic to a point where wireline facilities are available. Mesh backhaul configurations can be dynamically reconfigured to reroute traffic over different paths as conditions change.

### SEAMLESS LOW-LATENCY WLAN HANDOFFS

The vSZ-H supports seamless handoff for subscribers as they move from one Wi-Fi AP to another in the coverage area. It is not necessary for the user to re-authenticate as they move about. Their credentials are passed from access point to access point. Handoffs


are performed rapidly, and there is no impact on the application. The vSZ-H also supports Wi-Fi RAN load balancing.

### HOTSPOT 2.0-BASED ROAMING

Hotspot 2.0 enables seamless network discovery and selection along with seamless authentication using 802.1x/EAP. It represents the future of Wi-Fi roaming and has picked up a tremendous amount of support from throughout the wireless industry. The vSZ-H supports Hotspot 2.0 by enabling Ruckus APs to exchange information with Wi-Fi devices pre-association. The information that is exchanged includes details on roaming consortiums that are supported by that AP as well as information on backhaul capacity and loading. The Wi-Fi device then selects the best available AP and begins the authentication process. Hotspot 2.0 is automatic and requires no user intervention.

**FIGURE:2**

The built-in EMS in the vSZ-H provides user-friendly full-fledged FCAPS support and can be easily integrated with existing OSS/BSS systems.



## Operations and Administration (OAM)

### ELEMENT MANAGEMENT SYSTEM

With the built-in EMS, the vSZ-H supports rapid deployment and eliminates the need for separate and expensive management systems. The built-in EMS provides user-friendly full-fledged FCAPS support and can be easily integrated with existing OSS/BSS systems via a variety of interfaces ranging from traditional SNMP or CLI based interfaces to web programming friendly secure API based methods (RESTful JSON). See Figure 2.

### STATISTICS, KPIS AND REPORTS

The vSZ-H's built-in EMS provides rich near real-time statistics on subscribers (including client fingerprinting), APs, SSIDs, mesh backhaul, and the vSZ-H cluster itself. Reports ranging from hours to years can be generated for a variety of key performance indicators (KPIs) and exported out in multiple formats. For operators seeking richer information reporting, Ruckus also provides the SmartCell Insight (SCI) appliance for long-term storage, sophisticated data mining and analysis, and richer more complex reporting.

### ACCESS POINT CONFIGURATION AND MANAGEMENT

Access point configuration is a key function of the vSZ-H and especially important when rolling out networks with tens of thousands or hundreds of thousands of access points. In a Ruckus network deployment, access points will automatically connect to a pre-determined vSZ-H instance when they are installed in the field. They will identify themselves via MAC address and serial number, and then their configuration will be automatically downloaded along with their zone number. The configuration information for each AP is downloaded to the vSZ-H from an external provisioning system via a CSV file or an API (see figure





Figure 3: Automatic Access Point Configuration is the process by which APs installed in the field can have their configuration automatically downloaded to them via the vSZ-H.

**FIGURE:4**

The vSZ-H runs on a virtual machine established by the hypervisor. It in-turn runs atop the physical x86 blade servers. When deploying the vSZ-H in a data center, the existing cloud service management and orchestration function can interface with the vSZ-H through an API. This enables the rapid deployment of large numbers on managed WLAN networks in an extremely cost effective manner.



## MANAGED SERVICES

The vSZ-H's fully functional GUI provides concurrent role-based access control (RBAC) for viewing the Wi-Fi system resources and performance. With the support of partitioning for access in a secure manner, the vSZ-H allows service providers to give their managed services customers the ability to administer and monitor only the SSIDs over which they have control.

### Virtualizing the SmartZone

This is a key capability that will accelerate the deployment of managed WLAN services. It involves running the vSZ-H application and its OS on top of either the KVM or the VMware vSphere hypervisor. Virtualization enables a whole host of new capabilities including:

- Ability to dynamically add hardware resources as required to support the needs of a specific managed services customer, and those resources can be released just as easily. This enables a much more efficient use of data center resources.
- High availability by enabling the hypervisor to shift applications to different server modules to address failures. The vSZ-H application can also run in Active/Active mode for extremely high availability.
- The vSZ-H is well suited to deployment in a service provider's data center and it can support usage-based charging models
- Managed services customers can be assigned their own VM or they can share a VM in a multi-tenant

## KEY VSZ-H FEATURES

KEY VSZ-E FEATURES	
Monitoring	<ul style="list-style-type: none"> <li>• Enables quick views of the health of the network, APs, connected devices, and alerts</li> <li>• Provides detailed views of the AP status and client data</li> </ul>
Remote troubleshooting	<ul style="list-style-type: none"> <li>• Speeds problem resolution across multiple sites with easy drill-down menus</li> <li>• Enables IT to perform troubleshooting commands from the cloud</li> </ul>
Simplified deployment	<ul style="list-style-type: none"> <li>• Accelerates large-scale deployments by configuring APs in groups.</li> <li>• Simplifies configuration by applying consistent configurations and firmware to a group of APs</li> <li>• Offers flexible one-click firmware upgrades for all APs or a group of APs, using a cloud-hosted firmware server</li> </ul>
Reporting	<ul style="list-style-type: none"> <li>• Creates scheduled or on-demand network and security reports</li> <li>• Delivers PCI-compliance reports for compliance</li> </ul>
One-click provisioning	<ul style="list-style-type: none"> <li>• Downloads AP configurations from the cloud automatically</li> <li>• Requires no local IT support; any person onsite can plug in and power up the APs</li> </ul>

## SPECIFICATIONS

SUPPORTED CONFIGURATIONS	
Managed APs	<ul style="list-style-type: none"> <li>Up to 10,000 per vSZ-H</li> <li>Up to 30,000 in a 3+1 cluster</li> </ul>
Concurrent mobiles (UEs) / Stations	<ul style="list-style-type: none"> <li>Up to 100,000 users per vSZ-H instance</li> <li>Up to 300,000 users per vSZ-H cluster</li> </ul>
WLANs	<ul style="list-style-type: none"> <li>6,144 per vSZ-H</li> </ul>
Controller expansion	<ul style="list-style-type: none"> <li>Up to 4 controllers in a 3+1 active mode, supporting non-disruptive capacity expansion. Future releases will validate larger clusters</li> </ul>
Controller redundancy	<ul style="list-style-type: none"> <li>Distributed data preserving with 3+1 redundancy</li> </ul>

KEY FUNCTIONALITY	
Data offload	<ul style="list-style-type: none"> <li>Local offload of traffic from the AP directly to the internet or tunneled to a WLAN gateway</li> </ul>
Authentication protocols	<ul style="list-style-type: none"> <li>Open, 802.1x/EAP, PSK, WISPr, WPA, WPA2-AES, WPA-TKIP, WEP</li> <li>Fast EAP-SIM re-authentication</li> <li>EAP-SIM, EAP-AKA, EAP-AKA' over WLAN for 802.1x Wi-Fi Locations with the SCG AAA-Proxy functionality enabled</li> </ul>
AAA service	<ul style="list-style-type: none"> <li>RADIUS (AAA) proxy</li> </ul>
HotSpot 2.0	<ul style="list-style-type: none"> <li>Support for HotSpot 2.0 Release 2</li> </ul>
WISPr support	<ul style="list-style-type: none"> <li>WISPr 1.0 authentication</li> </ul>
Element management	<ul style="list-style-type: none"> <li>Secure multi-operator login (RBAC)</li> <li>Large scale (bulk) AP management tools</li> <li>Configuration audit trails</li> <li>Alarm and event notification (SNMP V2 / V3)</li> <li>Extensive statistics and reporting</li> <li>Integrated on-board remote accessible EMS</li> <li>RESTful APIs (JSON)</li> <li>CLI</li> </ul>

MODEL	# OF CLIENTS	vCPU (Core)	RAM (GB)	DISK VOL SIZE (GB)
<b>Virtual Smart Cell Gateway (vSZ)</b>				
100	2,000	2	8	100
500	10,000	4	9	100
1,000	20,000	4	11	100
2,500	50,000	6	15	300
10,000	100,000	16	48	600

## PRODUCT ORDERING INFORMATION

MODEL	DESCRIPTION
<b>Virtual SmartZone (vSZ)</b>	
L09-0001-SG00	AP management license for SZ-100/vSZ 3.X, 1 Ruckus AP
S01-0001-1LSG	Partner WatchDog support per SZ/vSZ AP, 1 YR
S01-0001-3LSG	Partner WatchDog support per SZ/vSZ AP, 3 YR
S01-0001-5LSG	Partner WatchDog support per SZ/vSZ AP, 5 YR
L09-VSCG-WW00	Virtual SmartZone 3.0 or newer software virtual appliance, 1 instance, includes 1 AP license
S01-VSCG-1L00	End user WatchDog support - vSZ-RTU, 1 YR
S01-VSCG-3L00	End user WatchDog support - vSZ-RTU, 3 YR
S01-VSCG-5L00	End user WatchDog support - vSZ-RTU, 5 YR